

Find the MAC Address of a Computer or Device

Stephanie Obodda - 2018-07-05 - Comments (0) - Support

A **Media Access Control (MAC) address** is a unique numeric identifier used to distinguish a device from others on a network. The address is assigned by the manufacturer, for Ethernet and Wi-Fi cards. Your device therefore is likely to have two MAC addresses.

[Windows](#)

[Mac \(OSX\)](#)

[Apple TV](#)

[Chromecast](#)

[Amazon Echo](#)

[PlayStation 2](#)

[PlayStation 3](#)

[Samsung Smart TV](#)

[Wii](#)

[Xbox](#)

[Xbox One](#)

[Xbox 360](#)

[Testing your Xbox Live Connection](#)

Windows

Get your computer's Wired or Wireless MAC address from the Command Prompt Screen:

1. Select the Start button.
2. Type command in the search box (Start->Run for Windows XP) and press Enter.
3. *At the Command Prompt, type ***ipconfig /all** Note: Be sure to put a space between ipconfig and /all!
4. Press Enter to list the connection information for your wired and/or wireless connections.
5. To find the Physical Address for your connection:
 - The wired physical address will be listed under Ethernet adapter Local Area

Connection

- The wireless physical address will be listed under Ethernet adapter Wireless Network Connection

6. Write down or copy/paste the addresses for future reference.

```
C:\WINDOWS\system32\cmd.exe
C:\>ipconfig /all

Windows IP Configuration

Host Name . . . . . : 
Primary Dns Suffix . . . . . : 
Node Type . . . . . : Hybrid
IP Routing Enabled. . . . . : No
WINS Proxy Enabled. . . . . : No
DNS Suffix Search List. . . . . : ad.brown.edu
                                      brown.edu

Ethernet adapter Local Area Connection:

   Connection-specific DNS Suffix . : 
   Description . . . . . : Realtek RTL8139 Family PCI Fast Ethernet NIC
   Physical Address. . . . . : 00-07-95-BE-80-1E
   DHCP Enabled. . . . . : Yes
   Autoconfiguration Enabled . . . . : Yes
   IP Address. . . . . : 128.148.177.106
   Subnet Mask . . . . . : 255.255.255.0
   Default Gateway . . . . . : 128.148.177.1
   DHCP Server . . . . . : 128.148.128.9
   DNS Servers . . . . . : 128.148.128.130
                           128.148.128.9
                           128.148.128.11
                           128.148.122.20
   Lease Obtained. . . . . : Tuesday, April 14, 2009 11:58:18 AM
   Lease Expires . . . . . : Tuesday, April 14, 2009 12:58:18 PM


Ethernet adapter Wireless Network Connection:

   Connection-specific DNS Suffix . : 
   Description . . . . . : Realtek RTL8192SE Wireless USB Network Adapter
   Physical Address. . . . . : 00-11-50-4B-CB-BD
   DHCP Enabled. . . . . : Yes
   Autoconfiguration Enabled . . . . : Yes
   IP Address. . . . . : 10.32.40.55
   Subnet Mask . . . . . : 255.255.255.0
   Default Gateway . . . . . : 10.32.40.1
   DHCP Server . . . . . : 10.32.40.1
   DNS Servers . . . . . : 128.148.128.130
                           128.148.128.9
                           128.148.128.11
                           128.148.122.20
   Lease Obtained. . . . . : Tuesday, April 14, 2009 12:00:09 PM
   Lease Expires . . . . . : Tuesday, April 14, 2009 1:00:09 PM

C:\>
```

Copy this information from the command prompt screen into a notepad document:

1. Right-click anywhere in the command prompt window and choose Select All.
2. Press Enter to copy the text from the Command Prompt screen.
3. Open up Notepad (Start->All Programs->Accessories->Notepad).
4. Right-click and choose Paste to put the information into the document.
5. Save and Print the document and keep it with your important papers.



Mac (OSX)

To get your computer's Wired or Wireless MAC address from the Terminal Screen:

1. Locate and open Terminal from Applications->Utilities->Terminal.
2. At the Terminal Prompt, type ifconfig and press Enter. This will list all of your network settings, including the physical addresses of your wired and wireless hardware.

3. To find the Physical Address for your connection:
 - > The wired physical address will be listed under en0
 - > The wireless physical address will be listed under en1
4. Write down or copy/paste the addresses into a document for future reference. You can also directly print it by going to Shell->Print. Keep this document with your important papers.

```

Terminal -- bash -- 92x42
Last login: Tue Apr 14 11:25:03 on ttys000
Alismac:~ ──┐ ifconfig
lo0: flags=8049<UP,LOOPBACK,RUNNING,MULTICAST> mtu 16384
    inet6 fe80::1::1::0 prefixlen 64 scopeid 0x1
    inet 127.0.0.1 netmask 0xff000000
    inet6 ::1 prefixlen 128
gif0: flags=8010<POINTOPOINT,MULTICAST> mtu 1280
stf0: flags=8<> mtu 1280
en0: flags=8063<UP,BROADCAST,SMART,RUNNING,SIMPLEX,MULTICAST> mtu 1500
    ether 00:16:cb:89:3d:52 ← Wired
    media: autoselect status: inactive
    supported media: autoselect 10baseT/UTP <half-duplex> 10baseT/UTP <full-duplex> 10ba
seT/UTP <full-duplex,hw-loopback> 10baseT/UTP <full-duplex,flow-control> 100baseTX <half-dup
lex> 100baseTX <full-duplex> 100baseTX <full-duplex,hw-loopback> 100baseTX <full-duplex,flow
-control> 1000baseT <full-duplex> 1000baseT <full-duplex,hw-loopback> 1000baseT <full-duplex
,flow-control> none
fv0: flags=8063<UP,BROADCAST,SMART,RUNNING,SIMPLEX,MULTICAST> mtu 2038
    lladdr 00:16:cb:ff:fe:54:ca:46
    media: autoselect <full-duplex> status: inactive
    supported media: autoselect <full-duplex>
en1: flags=8063<UP,BROADCAST,SMART,RUNNING,SIMPLEX,MULTICAST> mtu 1500
    inet6 fe80::216:cbff:fe00:54cb::en1 prefixlen 64 scopeid 0x6
    inet6 2002:8a10:3ae4:9:216:cbff:fe00:54cb prefixlen 64 deprecated autoconf
    inet6 fec8::9:216:cbff:fe00:54cb prefixlen 64 deprecated autoconf
    inet 128.148.179.244 netmask 0xfffffe00 broadcast 128.148.179.255
    ether 00:16:cb:86:54:cb ← Wireless
    media: autoselect status: active
    supported media: autoselect
en4: flags=8963<UP,BROADCAST,SMART,RUNNING,PROMISC,SIMPLEX,MULTICAST> mtu 1500
    inet6 fe80::21c:42ff:fe00:80en4 prefixlen 64 scopeid 0x7
    inet 10.211.55.2 netmask 0xfffffff0 broadcast 10.211.55.255
    ether 00:1c:42:00:00:06
    media: autoselect status: active
    supported media: autoselect
en5: flags=8963<UP,BROADCAST,SMART,RUNNING,PROMISC,SIMPLEX,MULTICAST> mtu 1500
    inet6 fe80::21c:42ff:fe00:90en5 prefixlen 64 scopeid 0x8
    inet 10.37.129.2 netmask 0xfffffff0 broadcast 10.37.129.255
    ether 00:1c:42:00:00:09
    media: autoselect status: active
    supported media: autoselect
Alismac:~ ──┐
  
```

Apple TV

- *On the box:* Look for the **Wireless ID** near the UPC label
- *On the Apple TV:* Go to **Menu > Settings > About** and look for the **Wireless ID**

Chromecast

PLEASE NOTE that Chromecasts do NOT currently work at Brown. Sorry!

In most cases, it will be listed on the page which asks you to select a wireless network (below are screenshots for Android and Mac). On a PC, you may have to click Settings to get to this page.


Connect Chromecast to your Wi-Fi

Wi-Fi network

Brown



MAC Address: 6C:AD



Amazon Echo

1. Download the Amazon Alexa app to your phone or computer and sign in with your Amazon account.
2. Connect to the wireless network transmitted by your Echo device.
3. The wireless MAC address for your Echo can be found at the bottom of the Echo Setup screen in the Alexa app.

PlayStation 2

1. Install the network adapter given in the installation guide or on the PlayStation 2 Network Adapter Web site. Once you have the network adapter installed you are ready to begin the ISP Setup process.
2. Power up the PlayStation 2 and load the Network Adaptor Startup Disc.
3. Once it has loaded, select ISP Setup and press X.
4. The ISP SETUP will begin to load, and you will be presented with a license agreement. Select Agree and press X to continue.
5. For connection type, choose Local Area Network (LAN) and press X to continue.



6. Select Automatic Configuration and press X to continue.



7. At the connection test screen, select Advanced and press X to continue.



8. At the Advanced Broadband Settings screen, make sure Automatic is selected. While you are at this screen, make note of the MAC Address at the bottom. You will need this number to register your game console.




Playstation 3

1. Power up the PlayStation 3 without any disc in the drive.
2. Once the PlayStation 3 operating system has loaded, select "Settings."
3. Once you are in "Settings" select "Network Settings."
4. When the "Network Settings" list appears, select the first option which is titled "Settings and Connection Status List."
5. The physical address will be listed under "MAC Address"

Samsung Smart TV

1. Go to your TV's menu and choose Network > Network Settings
2. Choose Wireless for your connection type
3. Choose to connect to the Brown-Guest network
4. On some Smart TVs, you will see the MAC Address on the next screen.
If it is not displayed, go back to the menu and choose Network > Network Status.



Wii

The Nintendo Wii is unable to access the Brown network via wireless connection and will


require the purchase and use of the Wii LAN Adapter.



1. When at the Wii menu screen, click the Wii icon in the lower left corner.




2. Select Wii Settings.




3. Click the arrow on the right side of the screen to advance to the next page of settings.




4. Select Internet.



5. Select Console Information.



6. The MAC address for your console will be displayed under the LAN Adapter MAC Address listing(the second line).



Xbox

1. Insert your Xbox Live DVD in the drive. The software will automatically run and update the Xbox dashboard to show the Xbox Live option. Once this is complete, eject the CD and make sure you have your network cable plugged into your Xbox and in the network port. Open the Settings menu.



2. From Settings, go to Network Settings.



3. Within the Network Settings Menu, go to IP Addresses.



4. Once in the IP Addresses Menu, be sure the configuration is set to Automatic.



5. Press B and go back to the Network Settings menu, then go to DNS Servers.



6. Once in the DNS Servers Menu, be sure the configuration is set to Automatic.



7. Press B and go back to the Network Settings menu, there you will then see the MAC address in the lower right hand part of the screen. Write this MAC address down somewhere.



Xbox One

If you are able to reach the main menu on your Xbox, follow the steps below to locate the wired MAC address of your console.

1. If you are signed into your profile, navigate to My Games & Apps. **Skip this step if you are not signed into a profile.
2. From there, select Settings.
3. In the settings pane, select Network.
4. Select Advanced Settings.
5. Record the Wired MAC address on this screen. It should be in the format "00:00:00:00:00:00."

Xbox 360

1. Go to the System area of the Xbox Dashboard and select Network Settings.



2. Select Edit Settings.




3. Under Basic Settings, check to make sure the IP Settings is on Automatic.



4. Now go to Additional Settings, select Advanced Settings.



5. At the bottom of this screen you'll see a heading called Wired MAC Address.




Testing your Xbox Live Connection

1. Once you have registered your Xbox 360 with the BGSU network, you can test your Xbox Live Connection. Go to the System area of the Xbox Dashboard and select Network Settings. From this menu then select "Test Xbox Live Connection".



2. The next screen will warn you that testing your network connection will sign everyone out. Select "Yes" to continue.



3. Testing of all Xbox Live connection will then take place.



4. To begin using your Xbox Live connection, Go to the Xbox Live area of the Xbox Dashboard and select the graphic that reads "Xbox Live".